

### FEATURES

- Available as "HR" (high reliability) screened per MIL-PRF-19500, JANTX level. Add "HR" suffix to base part number.
- Available as non-RoHS (Sn/Pb plating), standard, and as RoHS by adding "-PBF" suffix.

### MAXIMUM RATINGS

Parameter	Symbol	2SC3156	Unit
Collector-base voltage	$V_{CBO}$	900	V
Collector-emitter voltage	$V_{CEO}$	800	V
Emitter-base voltage	$V_{EBO}$	7.0	V
Collector current – continuous	$I_C$	6	A
Collector current – peak <sup>(1)</sup>	$I_{CM}$	20	A
Base current	$I_B$	3	A
Total power dissipation	$P_D$	120	W
Junction and storage temperature range	$T_J, T_{stg}$	-55 to 150	°C

Note 1: Pulse width  $\leq 300\mu s$ , duty cycle  $\leq 10\%$ .

### ELECTRICAL CHARACTERISTICS ( $T_C = 25^\circ C$ unless otherwise noted)


Parameter	Symbol	Conditions	2SC3156			Unit
			Min	Typ	Max	
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C = 5mA, R_{BE} = \infty$	800	-	-	V
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C = 1mA, I_E = 0$	900	-	-	V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E = 1mA, I_C = 0$	7	-	-	V
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = 3.0A, I_B = 0.6A$	-	-	2.0	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C = 3.0A, I_B = 0.6A$	-	-	1.5	V
Collector cutoff current	$I_{CBO}$	$V_{CB} = 800V, I_E = 0$	-	-	10	$\mu A$
Emitter cutoff current	$I_{EBO}$	$V_{EB} = 5V, I_C = 0$	-	-	10	$\mu A$
DC current gain	$h_{FE}$	$I_C = 0.4A, V_{CE} = 5V$	10	-	-	-
		$I_C = 2.0A, V_{CE} = 5V$	8	-	-	-
Output capacitance	$C_{ob}$	$I_E = 0, V_{CB} = 10V, f = 1MHz$	-	120	-	pF
Transition frequency	$f_T$	$I_C = 0.4A, V_{CE} = 10V$	-	15	-	MHz
Turn-on time	$t_{on}$	$I_C = 4A, I_{B1} = 0.8A, I_{B2} = -1.6A, V_{CC} = 400V, R_L = 100\Omega$	-	-	1.0	$\mu s$
Storage time	$t_s$		-	-	2.5	$\mu s$
Fall time	$t_f$		-	-	0.7	$\mu s$

# 2SC3156

SILICON NPN TRANSISTOR

## MECHANICAL CHARACTERISTICS

<b>Case:</b>	TO-3
<b>Marking:</b>	Alpha-Numeric
<b>Polarity:</b>	See below



	TO-3			
	Inches		Millimeters	
	Min	Max	Min	Max
CD	-	0.875	-	22.220
CH	0.250	0.380	6.860	9.650
HT	0.060	0.135	1.520	3.430
BW	-	1.050	-	26.670
HD	0.131	0.188	3.330	4.780
LD	0.038	0.043	0.970	1.090
LL	0.312	0.500	7.920	12.700
BL	1.550 REF		39.370 REF	
MHS	1.177	1.197	29.900	30.400
PS	0.420	0.440	10.670	11.180
S1	0.655	0.675	16.640	17.150