

KBPC10005 SERIES

SINGLE PHASE BRIDGE RECTIFIER

FEATURES

- Available as "HR" (high reliability) screened per MIL-PRF-19500, JANTX level. Add "HR" suffix to base part number.
- Available as non-RoHS (Sn/Pb plating), standard, and as RoHS by adding "-PBF" suffix.

MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)


Rating	Symbol	KBPC10005	KBPC1001	KBPC1002	KBPC1004	KBPC1006	KBPC1008	KBPC1010	Unit
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum average forward output rectified current at $T_A = 55^\circ\text{C}$	$I_{F(AV)}$	10							Amps
Peak forward surge current single half-sine wave superimposed on rated load	I_{FSM}	200							Amps
Operating temperature range	T_C	-55 to +125							$^\circ\text{C}$
Storage temperature range	T_{stg}	-55 to +150							$^\circ\text{C}$
Typical junction capacitance	C_j	300							pF

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

Characteristic	Symbol	KBPC10005	KBPC1001	KBPC1002	KBPC1004	KBPC1006	KBPC1008	KBPC1010	Units
Maximum forward voltage drop per element @ 5.0 peak	V_F	1.2							Volts
Maximum reverse current at rated DC blocking voltage per element $T_A = 25^\circ\text{C}$	I_R	1.0							μA

MECHANICAL CHARACTERISTICS

Case	Digi R
Marking	Body painted, alpha-numeric
Pin out	See below



	Digi R			
	Inches		Millimeters	
	Min	Max	Min	Max
A	1.120	1.135	28.400	28.829
B	0.618	0.685	15.700	16.700
C	0.530	0.580	13.400	14.732
D	0.688	0.728	17.400	18.500
F	0.200	0.220	5.100	5.588
G	0.618	0.658	15.700	16.700
H	0.425	0.440	10.795	11.176
J	0.028	0.032	0.710	0.810
K	0.826	0.905	21.000	23.000
L	0.240	0.260	6.096	6.604
M	0.090	0.100	2.300	2.500

KBPC10005 SERIES

SINGLE PHASE BRIDGE RECTIFIER

